



APX LED High Bay

12,000 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution

12,000 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution – 123 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

Product data

General Information		
Lamp Source Code	LED	
Colour Temperature	4000 K	
CRI	80	
Photometric Distribution Type	Direct	
Mounting	Suspended	
Operating and Electrical		
Voltages	120/208/240/277/347/480/UNIV V	
Luminaire Input Watts	96	
Mechanical and Housing		
Fixture Size	48 in	
Initial Performance (IEC Co	mpliant)	
Luminaire Lumens	12000	

Efficacy	123 lm/W	
Product Data		
Order product name	APX12LL40-UNV	
EAN/UPC - Product	784197052676	
Order code	APX12LL40-UNV-A	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box 1		
Material Nr. (12NC)	912401272303	
Net Weight (Piece)	0.001 kg	
Catalog Number	APX12LL40-UNV-A	
Catalog Number Description	12,000 Nominal Delivered Lumens, 4000K, 80 CRI,	
	Aisle Distribution	