



APX LED High Bay

APX08LL40-UNV

8,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Clear Polycarbonate Lens - 124 Im/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

Product data

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	76
Mechanical and Housing	
Fixture Size	48 in
Initial Performance (IEC Compliant)	
Luminaire Lumens	8000
Efficacy	124 lm/W

Product Data	
Order product name	APX08LL40-UNV
EAN/UPC - Product	784197056483
Order code	912401272304
Local order code	9705648
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401272304
Net Weight (Piece)	0.001 kg
Commercial Code	APX08LL40-UNV-LCP
Catalog Number Description	8,000 Nominal Delivered Lumens, 4000K, 80 CRI, General
	Distribution, Clear Polycarbonate Lens
Quick Ship	-

APX LED High Bay



© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2018, August 7 - data subject to change