



APX LED High Bay

APX24LL40-UNV

24,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow Distribution - 120 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

Product data

General Information		
Lamp Source Code	LED	
Color Temperature	4000K	
CRI	80	
Photometric Distribution Type	Direct	
Mounting	Suspended	
Operating and Electrical		
Voltages	120/208/240/277/347/480/UNIV V	
Luminaire Input Watts	191	
Mechanical and Housing		
Fixture Size	48 in	
Initial Performance (IEC Compliant)		
Luminaire Lumens	24000	
Efficacy	120 lm/W	

Product Data	
Order product name	APX24LL40-UNV
EAN/UPC - Product	784197056544
Order code	912401272309
Local order code	9705654
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401272309
Net Weight (Piece)	0.001 kg
Commercial Code	APX24LL40-UNV-N
Catalog Number Description	24,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow
	Distribution
Quick Ship	-

Datasheet, 2018, August 7 data subject to change

APX LED High Bay

