



APX LED High Bay

24,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution

24,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution - 120 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

Product data

General Information		Efficacy 120 lm/W	
Lamp Source Code	LED		
Colour Temperature	4000 K	Product Data	
CRI	80	Order product name	APX24LL40-UNV
Photometric Distribution Type	Direct	EAN/UPC - Product	784197056551
Mounting	Suspended	Order code	APX24LL40-UNV-M
Operating and Electrical		Numerator - Quantity Per Pack	1
Voltages	120/208/240/277/347/480/UNIV V	Numerator - Packs per outer box	1
Luminaire Input Watts	191	Material Nr. (12NC)	912401272310
Mechanical and Housing		Net Weight (Piece)	0.001 kg
Fixture Size	48 in	Catalog Number	APX24LL40-UNV-M
Initial Performance (IEC Compliant)		Catalog Number Description	24,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution
Luminaire Lumens	24000		