PHILIPS

Lighting



APX LED High Bay

APX20LL40-UNV

20,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow Distribution - 123 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

Product data

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended

Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	168

Mechanical and Housing	
Fixture Size	48 in

Initial Performance (IEC Compliant)	
Luminaire Lumens	20000
Efficacy	123 lm/W

Product Data	
Order product name	APX20LL40-UNV
EAN/UPC - Product	784197057220
Order code	912401272329
Local order code	9705722
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401272329
Net Weight (Piece)	0.001 kg
Commercial Code	APX20LL40-UNV-N
Catalog Number Description	20,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow Distribution
Quick Ship	-



© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com
2018, August 7 - data subject to change