



## **APX LED High Bay**

## 20,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Acrylic Lens

20,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Acrylic Lens - 109 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

## **Product data**

General Information	
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
-	
Voltages	120/208/240/277/347/480/UNIV V
	120/208/240/277/347/480/UNIV V 168
Voltages	
Voltages	
Voltages Luminaire Input Watts	
Voltages Luminaire Input Watts  Mechanical and Housing	168
Voltages Luminaire Input Watts  Mechanical and Housing	168 48 in

Efficacy	109 lm/W
Product Data	
Order product name	APX20LL40-UNV
EAN/UPC - Product	784197056360
Order code	APX20LL40-UNV-LFA
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401272331
Net Weight (Piece)	0.001 kg
Catalog Number	APX20LL40-UNV-LFA
Catalog Number Description	20,000 Nominal Delivered Lumens, 4000K, 80 CRI,
	General Distribution, Frosted Acrylic Lens

Datasheet, 2019, May 6 data subject to change