



## **APX LED High Bay**

## 16,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Polycarbonate Lens

16,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Polycarbonate Lens - 127 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

## **Product data**

| General Information           |                                | Initial Performance (IEC Co    | Initial Performance (IEC Compliant)             |  |
|-------------------------------|--------------------------------|--------------------------------|---|--|
| Lamp Source Code              | LED                            | Luminaire Lumens               | 16000   |  |
| Colour Temperature            | 4000 K                         | Efficacy                       | 127 lm/W  |  |
| CRI                           | 80                             |                                |   |  |
| Photometric Distribution Type | Direct                         | Product Data                   |   |  |
| Mounting                      | Suspended                      | Order product name             | APX16LL40-UNV                                   |  |
|                               |                                | EAN/UPC - Product              | 784197056728                                    |  |
| Operating and Electrical      |                                | Order code                     | APX16LL40-UNV-LFP                               |  |
| Voltages                      | 120/208/240/277/347/480/UNIV V | Numerator - Quantity Per Pack  | 1   |  |
| Luminaire Input Watts         | 123                            | Numerator - Packs per outer bo | Numerator - Packs per outer box 1               |  |
|                               |                                | Material Nr. (12NC)            | 912401272338                                    |  |
| Mechanical and Housing        |                                | Net Weight (Piece)             | 0.001 kg  |  |
| Fixture Size                  | 48 in                          | Catalog Number                 | APX16LL40-UNV-LFP                               |  |
|                               |                                | Catalog Number Description     | 16,000 Nominal Delivered Lumens, 4000K, 80 CRI, |  |
|                               |                                |                                | General Distribution Frosted Polycarbonate Lens |  |



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, May 6 - data subject to change