



SofTrace Surface LED

2SST50L835-4-DS-UNV

2x4, Surface, 5000 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth

SofTrace Surface LED brings new meaning to the concept of combining style with performance. Equipped with a fresh streamlined design and innovative technology, SofTrace provides a huge step forward for the lighting industry. The sleek profile design belies the true “horsepower under the hood”. With efficiency levels exceeding 95% and lumens per Watt as great as 87, an architectural product now delivers leading edge performance for the most environmentally conscious user.

Product data

General Information	
Lamp Source Code	LED
Color Temperature	3500K
CRI	80
Photometric Distribution Type	Direct
Mounting	Surface
Operating and Electrical	
Voltages	120/277/347 V
Luminaire Input Watts	49
Mechanical and Housing	
Fixture Size	2 ft x 4 ft
Shape	Rectangular
Initial Performance (IEC Compliant)	
Luminaire Lumens	5000

Product Data	
Order product name	2SST50L835-4-DS-UNV
EAN/UPC - Product	784197061029
Order code	912401272586
Local order code	9706102
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401272586
Net Weight (Piece)	0.001 kg
Commercial Code	2SST50L835-4-DS-UNV-DIM
Catalog Number Description	2x4, Surface, 5000 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth
Quick Ship	-

SofTrace Surface LED

