

SofTrace Surface LED

2SST30L835-2-DS-UNV

2x2, Surface, 3000 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth

SofTrace Surface LED brings new meaning to the concept of combining style with performance. Equipped with a fresh streamlined design and innovative technology, SofTrace provides a huge step forward for the lighting industry. The sleek profile design belies the true “horsepower under the hood”. With efficiency levels exceeding 95% and lumens per Watt as great as 87, an architectural product now delivers leading edge performance for the most environmentally conscious user.

Product data

General Information	
Lamp Source Code	LED
Color Temperature	3500K
CRI	80
Photometric Distribution Type	Direct
Mounting	Surface

Operating and Electrical	
Voltages	120/277/347 V
Luminaire Input Watts	33

Mechanical and Housing	
Fixture Size	2 ft x 2 ft
Shape	Square

Initial Performance (IEC Compliant)	
Luminaire Lumens	3000

Product Data	
Order product name	2SST30L835-2-DS-UNV
EAN/UPC - Product	784197078980
Order code	912401273804
Local order code	9707898
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401273804
Net Weight (Piece)	0.001 kg
Commercial Code	2SST30L835-2-DS-UNV-DIM
Catalog Number Description	2x2, Surface, 3000 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth
Quick Ship	-



© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com
2018, July 24 - data subject to change