



APX LED High Bay

24,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Clear Polycarbonate Lens

24,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Clear Polycarbonate Lens - 116 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	191
Mechanical and Housing	
Fixture Size	48 in

Initial Performance (IEC Compliant)	
Luminaire Lumens	24000
Efficacy	116 lm/W
Product Data	
Order product name	APX24LL40-UNV
EAN/UPC - Product	784197087005
Order code	APX24LL40-UNV-M-LCP
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401274412
Net Weight (Piece)	0.001 kg
Catalog Number	APX24LL40-UNV-M-LCP
Catalog Number Description	24,000 Nominal Delivered Lumens, 4000K, 80 CRI,
	Medium Distribution, Clear Polycarbonate Lens

Datasheet, 2019, May 6 data subject to change



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.