



## **APX LED High Bay**

## 8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Wide Distribution, Clear Polycarbonate Lens

8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Wide Distribution, Clear Polycarbonate Lens - 121 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

## **Product data**

General Information	
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	76
Mechanical and Housing	
Fixture Size	48 in
Initial Performance (IEC Compliant)	

Efficacy	121 lm/W
Product Data	
Order product name	APX08LL40-UNV
EAN/UPC - Product	784197106393
Order code	APX08LL40-UNV-W-LCP
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401275331
Net Weight (Piece)	0.001 kg
Net Weight (Piece)  Catalog Number	0.001 kg APX08LL40-UNV-W-LCP

Datasheet, 2019, May 6 data subject to change