



## **APX LED High Bay**

## APX08LL40-UNV

8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Frosted Acrylic Lens - 112 Im/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

## Product data

General Information		
Lamp Source Code	LED	
Color Temperature	4000K	
CRI	80	
Photometric Distribution Type	Direct	
Mounting	Suspended	
Operating and Electrical		
Voltages	120/208/240/277/347/480/UNIV V	
Luminaire Input Watts	76	
Mechanical and Housing		
Fixture Size	48 in	
Initial Performance (IEC Compliant)		
Luminaire Lumens	8000	
Efficacy	112 lm/W	

Product Data	
Order product name	APX08LL40-UNV
EAN/UPC - Product	784197188726
Order code	912401278850
Local order code	9718872
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401278850
Net Weight (Piece)	0.001 kg
Commercial Code	APX08LL40-UNV-M-LFA
Catalog Number Description	8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium
	Distribution, Frosted Acrylic Lens
Quick Ship	-

**APX LED High Bay** 



© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2018, August 7 - data subject to change