



APX LED High Bay

8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Frosted Acrylic Lens

8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Frosted Acrylic Lens - 112 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Voltages Luminaire Input Watts	120/208/240/277/347/480/UNIV V 76
Luminaire Input Watts	
Luminaire Input Watts Mechanical and Housing	76
Luminaire Input Watts Mechanical and Housing	76 48 in

Efficacy	112 lm/W
Product Data	
Order product name	APX08LL40-UNV
EAN/UPC - Product	784197188726
Order code	APX08LL40-UNV-M-LFA
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401278850
Net Weight (Piece)	0.001 kg
Catalog Number	APX08LL40-UNV-M-LFA
Catalog Number Description	8,000 Nominal Delivered Lumens, 4000K, 80 CRI,
	Medium Distribution, Frosted Acrylic Lens

Datasheet, 2019, May 6 data subject to change