

LBX LED Linear Suspended

LBX40L840-UNV

4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI, Wide Distribution - 148 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

General Information	
Color Temperature	4000K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended

Operating and Electrical	
Voltages	347/UNIV V
Luminaire Input Watts	31

Mechanical and Housing	
Fixture Size	48 in
Shape	Linear

Initial Performance (IEC Compliant)	
Luminaire Lumens	4000
Efficacy	148 lm/W

Product Data	
Order product name	LBX40L840-UNV
EAN/UPC - Product	784197190972
Order code	912401279084
Local order code	9719097
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401279084
Net Weight (Piece)	0.001 kg
Commercial Code	LBX40L840-UNV-W
Catalog Number Description	4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI, Wide Distribution
Quick Ship	-

© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.