



LBX LED Linear Suspended

4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI, Wide Distribution

4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI, Wide Distribution - 148 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

General Information	
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	347/UNIV V
Luminaire Input Watts	31
Mechanical and Housing	
Fixture Size	48 in
Shape	Linear

Initial Performance (IEC Compliant)	
Luminaire Lumens	4000
Efficacy	148 lm/W
Product Data	
Order product name	LBX40L840-UNV
EAN/UPC - Product	784197190972
Order code	LBX40L840-UNV-W
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401279084
Net Weight (Piece)	0.001 kg
Catalog Number	LBX40L840-UNV-W

Datasheet, 2019, May 6 data subject to change

LBX LED Linear Suspended

Catalog Number Description

4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI,

Wide Distribution



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.