



LBX LED Linear Suspended

LBX55L840-UNV

4', 5,500 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution - 147 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

General Information		Efficacy 147 lm/W	
Color Temperature	4000K		
CRI	80		
Photometric Distribution Type	Direct		
Mounting	Suspended		
Operating and Electrical		Product Data	
Voltages	347/UNIV V	Order product name	LBX55L840-UNV
Luminaire Input Watts	41	EAN/UPC - Product	784197191108
Mechanical and Housing		Order code	912401279095
Fixture Size	48 in	Local order code	9719110
Shape	Linear	Numerator - Quantity Per Pack	1
Initial Performance (IEC Compliant)		Numerator - Packs per outer box	1
Luminaire Lumens	5500	Material Nr. (12NC)	912401279095
		Net Weight (Piece)	0.001 kg
		Commercial Code	LBX55L840-UNV-A
		Catalog Number Description	4', 5,500 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution
		Quick Ship	-

