

# LBX LED Linear Suspended

## LBX55L840-UNV

4', 5,500 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Flat Diffuse Lens - 127 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

### Product data

| General Information | |
|---|---|
| **Color Temperature** | 4000K |
| **CRI** | 80 |
| **Photometric Distribution Type** | Direct |
| **Mounting** | Suspended |

| Operating and Electrical | |
|---|---|
| **Voltages** | 347/UNIV V |
| **Luminaire Input Watts** | 41 |

| Mechanical and Housing | |
|---|---|
| **Fixture Size** | 48 in |
| **Shape** | Linear |

| Initial Performance (IEC Compliant) | |
|---|---|
| **Luminaire Lumens** | 5500 |
| **Efficacy** | 127 lm/W |

| Product Data | |
|---|---|
| **Order product name** | LBX55L840-UNV |
| **EAN/UPC - Product** | 784197191146 |
| **Order code** | 912401279098 |
| **Local order code** | 9719114 |
| **Numerator - Quantity Per Pack** | 1 |
| **Numerator - Packs per outer box** | 1 |
| **Material Nr. (12NC)** | 912401279098 |
| **Net Weight (Piece)** | 0.001 kg |
| **Commercial Code** | LBX55L840-UNV-FD |
| **Catalog Number Description** | 4', 5,500 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Flat Diffuse Lens |
| **Quick Ship** | - |

© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.