



LBX LED Linear Suspended

LBX140L840-UNV

8', 14,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution - 148 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

General Information	
Color Temperature	4000K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended

Operating and Electrical	
Voltages	347/UNIV V
Luminaire Input Watts	110

Mechanical and Housing	
Fixture Size	96 in
Shape	Linear

Initial Performance (IEC Compliant)	
Luminaire Lumens	14000

Efficacy	148 lm/W
----------	----------

Product Data	
Order product name	LBX140L840-UNV
EAN/UPC - Product	784197192259
Order code	912401279195
Local order code	9719225
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401279195
Net Weight (Piece)	0.001 kg
Commercial Code	LBX140L840-UNV
Catalog Number Description	8', 14,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution
Quick Ship	-

LBX LED Linear Suspended

