



# APX LED High Bay

## APX12LL40-UNV

12,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Clear Polycarbonate Lens - 118 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

### Product data

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	96
Mechanical and Housing	
Fixture Size	48 in
Initial Performance (IEC Compliant)	
Luminaire Lumens	12000
Efficacy	118 lm/W

Product Data	
Order product name	APX12LL40-UNV
EAN/UPC - Product	784197335434
Order code	912401280202
Local order code	9733543
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401280202
Net Weight (Piece)	0.001 kg
Commercial Code	APX12LL40-UNV-M-LCP
Catalog Number Description	12,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Clear Polycarbonate Lens
Quick Ship	-

APX LED High Bay

