



SofTrace Air LED

2x4, Air Handling, 6300 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Ribbed

2x4, Air Handling, 6300 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Ribbed

SofTrace Air LED brings new meaning to the concept of combining style with performance. Equipped with a fresh streamlined design and innovative technology, SofTrace provides a huge step forward for the lighting industry. The sleek profile design belies the true “horsepower under the hood”. With efficiency levels exceeding 95% and lumens per Watt as great as 87, an architectural product now delivers leading edge performance for the most environmentally conscious user.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	3500K
CRI	80
Photometric Distribution Type	Direct
Mounting	Recessed
Operating and Electrical	
Voltages	120/277/347 V
Luminaire Input Watts	65
Mechanical and Housing	
Fixture Size	2 ft x 4 ft
Initial Performance (IEC Compliant)	
Luminaire Lumens	6300

Product Data	
Order product name	2STGA63L835-4-D-UNV
EAN/UPC - Product	784197246655
Order code	2STGA63L835-4-D-UNV-DIM
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401282360
Net Weight (Piece)	0.001 kg
Catalog Number	2STGA63L835-4-D-UNV-DIM
Catalog Number Description	2x4, Air Handling, 6300 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Ribbed

