



## SofTrace Recessed LED

## 2STG32L8TW-2-D-UNV

2x2 Tunable White, 3200 Nominal Delivered Lumens, 80 CRI, 2700-6500K, Diffuse (Smooth)

SofTrace LED brings new meaning to the concept of combining style with performance. Equipped with a fresh streamlined design and innovative technology, SofTrace provides a huge step forward for the lighting industry. The sleek profile design belies the true "horsepower under the hood". With efficiency levels exceeding 95% and lumens per Watt as great as 87, an architectural product now delivers leading edge performance for the most environmentally conscious user.

## **Product data**

General Information	
Color Temperature	6500K
CRI	80
Photometric Distribution Type	Direct
Mounting	Recessed
Operating and Electrical	
Voltages	120/277/347/UNIV V
Luminaire Input Watts	35
Mechanical and Housing	
Fixture Size	2 ft x 2 ft
Shape	Square
Initial Performance (IEC Compliant)	
Luminaire Lumens	3200

Product Data	
Order product name	2STG32L8TW-2-D-UNV
EAN/UPC - Product	784197259495
Order code	912401282763
Local order code	9725949
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401282763
Net Weight (Piece)	0.001 kg
Commercial Code	2STG32L8TW-2-D-UNV-DTW
Catalog Number Description	2x2 Tunable White, 3200 Nominal Delivered Lumens, 80 CRI,
	2700-6500K, Diffuse (Smooth)
Quick Ship	-

Datasheet, 2018, June 7 data subject to change