



SofTrace Air LED

2x4, Air Handling, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth

2x4, Air Handling, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth

SofTrace Air LED brings new meaning to the concept of combining style with performance. Equipped with a fresh streamlined design and innovative technology, SofTrace provides a huge step forward for the lighting industry. The sleek profile design belies the true “horsepower under the hood”. With efficiency levels exceeding 95% and lumens per Watt as great as 87, an architectural product now delivers leading edge performance for the most environmentally conscious user.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	3500K
CRI	80
Photometric Distribution Type	Direct
Mounting	Recessed
Operating and Electrical	
Voltages	120/277/347 V
Luminaire Input Watts	41
Mechanical and Housing	
Fixture Size	2 ft x 4 ft
Initial Performance (IEC Compliant)	
Luminaire Lumens	4200

Product Data	
Order product name	2STGA42L835-4-DS-UNV
EAN/UPC - Product	784197095963
Order code	2STGA42L835-4-DS-UNV-DIM
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401287022
Net Weight (Piece)	0.001 kg
Catalog Number	2STGA42L835-4-DS-UNV-DIM
Catalog Number Description	2x4, Air Handling, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth

SofTrace Air LED

