



iUL516 Inground

Inground, Composite, Narrow Flood, Bronze, 7W LED, 3000K, 12V

Inground, Composite, Narrow Flood, Bronze, 7W LED, 3000K, 12V - 100 lm/W

Hadco's iUL516 is a compact low voltage composite landscape luminaire for inground applications. Lamping sources include 35W maximum MR16 bi-pin lamp and LED. Construction includes a one-piece injection molded ULTEM® High Performance Polymer composite body with a single piece injected lens ring and gasketed lens. Twist-off operation for ease of maintenance.

Product data

| General information | |
|-------------------------------|-------------------|
| Lamp Source Code | LED |
| Lamp Watts | 7 |
| Number of Lamps | 1 |
| Colour Temperature | 3000 K |
| CRI | 80 |
| Photometric Distribution Type | Medium |
| Mounting | In Ground |
| Number Of Pieces | 1 |
| Operating and electrical | |
| Voltages | 12 V |
| Luminaire Input Watts | 7 |
| Conduit Connection | 7/8 inch knockout |
| Mechanical and housing | |
| Enclosure | Metal and Plastic |

| Initial performance (IEC compliant) | |
|-------------------------------------|---|
| Luminaire Lumens | 600 |
| Efficacy | 100 lm/W |
| Product data | |
| Order product name | INGROUND,MICRO,12V,LED,MR16 LMP |
| Order code | IUL516-HLED7NFW |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 1 |
| Material Nr. (12NC) | 912401335049 |
| Net Weight (Piece) | 0.001 kg |
| Catalog Number | IUL516-HLED7NFW |
| Catalog Number Description | Inground, Composite, Narrow Flood, Bronze, 7W LED, 3000K, 12V |

