



Ocean Bollard LED

BGP708 GRN9/830 II PSU WRN SI

LED GreenLine 900 lm, 830 warm white, Safety class II, Asymmetrical wide beam, Silver

The robust Ocean Bollard LED combines a distinctive family design with an innovative and efficient light distribution. It is ideal for marking out and punctuating outdoor spaces as well as guiding pedestrians.

Product data

General Information		Glow-wire test	
Lamp family code	GRN9 [LED GreenLine 900 lm]	EU RoHS compliant	Yes
Light source replaceable	No	Light Technical	
Number of gear units	1 unit	Upward light output ratio	0.03
Gear	EB [Electronic]	Luminous Flux	842 lm
Driver included	Yes	Standard tilt angle posttop	0°
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.	Standard tilt angle side entry	0°
Light source engine type	LED	Correlated Color Temperature (Nom)	3000 K
Service tag	Yes	Luminous Efficacy (rated) (Nom)	70 lm/W
Lighting Technology	LED	Color rendering index (CRI)	≥80
CE mark	Yes	Number of light sources	9
Warranty period	1 years	Light source color	830 warm white
Flammability mark	-	Optical cover type	Polycarbonate bowl/cover
ENEC mark	-	Luminaire light beam spread	360°
		Optic type outdoor	Asymmetrical wide beam
		Operating and Electrical	
		Input Voltage	220/240 V
		Line Frequency	50 to 60 Hz

Ocean Bollard LED

Inrush current	15 A
Inrush time	360 ms
Power Consumption	12 W
Power Factor (Fraction)	0.99
Connection	Screw connection block 3-pole
Cable	-
Number of products on MCB of 16 A type B	23

Temperature

Ambient temperature range	-20 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit regulating
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Silver
Mounting device	Baseplate
Optical cover shape	Wide
Optical cover finish	Clear
Overall height	931 mm
Overall diameter	270 mm
Effective projected area	0 m²

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
-------------------------	--

Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	EN61547 (L-L 6kV, L-G 8kV) kV
Sustainability rating	-
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-5%
Initial chromaticity	0.44,0.41
Power consumption tolerance	+/-5%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 100000 h	L80


Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable

Product Data

Order product name	BGP708 GRN9/830 II PSU WRN SI
Full product name	BGP708 GRN9/830 II PSU WRN SI
Full product code	871869693870600
Order code	912401451601
Material Nr. (12NC)	912401451601
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696938706
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696938706

Dimensional drawing



Ocean Bollard LED

