



## EcoForm LED site and area G2 - small (ECF-S)

EcoForm, Small, 32 LEDs, 1A, 4000K, Generation 2, Type 4, Bronze

EcoForm, Small, 32 LEDs, 1A, 4000K, Generation 2, Type 4, Bronze - 133 lm/W

In any outdoor site and area project, the next generation of Gardco EcoForm LED site and area luminaires are more than sources of illumination. they offer the best of all worlds: saving energy, saving time, and saving money for significant and enduring value. It's not just about meeting technical requirements. It's about looking out for the best interests of your customers, and going the extra mile to uncover new savings and conveniences!

## **Product data**

General information	
Service tag	Yes
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	70
Photometric Distribution Type	Type IV
Mounting	Pole Arm Wall
B.U.G. Rating	B2U0G3
Awards	DLC QPL
Number Of Pieces	1

Buy American Compliant Products	Yes
Operating and electrical	
Voltages	120/277/UNIV V
Luminaire Input Watts	106 W
Conduit Connection	7/8 inch knockout
Mechanical and housing	
Enclosure	Metal and Plastic

Datasheet, 2023, March 22 data subject to change

## EcoForm LED site and area G2 - small (ECF-S)

Approval and application		
Safety Listing	UL	
Energy Certifications	IDA Dark Sky Approved cULus DLC Standard DLC	
	Premium	
IP Rating	IP65 [ Dust penetration-protected, jet-proof]	
Vibration Rating	3.0G	
Initial performance (IEC compliant)		
Luminaire Lumens	14000	
Efficacy	133 lm/W	
Application conditions		
Ambient temperature range	-40 to +40 °C	
Max Ambient Temp	+40 °C	
Min Ambient Temp	-40 °C	

Min Ambient Temp-DUP(do not use) -40 °C	
Product data	
Order product name	RS-ECF-S-32L-1A-NW-G2-AR-4-UNV-BZ
EAN/UPC - Product	190096018086
Order code	RS-ECF-S-32L-1A-NW-G2-AR-4-UNV-BZ
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401466004
Net Weight (Piece)	13.202 kg
Catalog Number	RS-ECF-S-32L-1A-NW-G2-AR-4-UNV-BZ
Catalog Number Description	EcoForm, Small, 32 LEDs, 1A, 4000K, Generation 2,
	Type 4, Bronze

