



EcoForm LED site and area G2 - small (ECF-S)

EcoForm, Small, 48 LEDs, 1A, 4000K, Generation 2, Type 4, Medium Grey

EcoForm, Small, 48 LEDs, 1A, 4000K, Generation 2, Type 4, Medium Grey - 132 lm/W

In any outdoor site and area project, the next generation of Gardco EcoForm LED site and area luminaires are more than sources of illumination. they offer the best of all worlds: saving energy, saving time, and saving money for significant and enduring value. It's not just about meeting technical requirements. It's about looking out for the best interests of your customers, and going the extra mile to uncover new savings and conveniences!

Product data

General information		Buy American Compliant Products Yes	
Service tag	Yes		
Lamp Source Code	LED	Operating and electrical	
Colour Temperature	4000 K	Voltages	120/277/UNIV V
CRI	70	Luminaire Input Watts	159
Photometric Distribution Type	Type IV	Conduit Connection	7/8 inch knockout
Mounting	Pole Arm Wall	Mechanical and housing	
B.U.G. Rating	B3U0G4	Enclosure	Metal and Plastic
Awards	DLC QPL		
Number Of Pieces	1		

EcoForm LED site and area G2 - small (ECF-S)

Approval and application

Safety Listing	UL
Energy Certifications	IDA Dark Sky Approved cULus DLC Standard DLC Premium
IP Rating	IP65 [Dust penetration-protected, jet-proof]
Vibration Rating	3.0G

Initial performance (IEC compliant)

Luminaire Lumens	20900
Efficacy	132 lm/W

Application conditions

Ambient temperature range	-40 to +40 °C
Max Ambient Temp	+40 °C
Min Ambient Temp	-40 °C

Min Ambient Temp-DUP(do not use) -40 °C

Product data

Order product name	RS-ECF-S-48L-1A-NW-G2-AR-4-UNV-MGY
EAN/UPC - Product	190096018154
Order code	RS-ECF-S-48L-1A-NW-G2-AR-4-UNV-MGY
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401466011
Net Weight (Piece)	13.202 kg
Catalog Number	RS-ECF-S-48L-1A-NW-G2-AR-4-UNV-MGY
Catalog Number Description	EcoForm, Small, 48 LEDs, 1A, 4000K, Generation 2, Type 4, Medium Grey

