



EcoForm LED site and area G2 - small (ECF-S)

RS-ECF-S-64L-1A-NW-G2-AR-3-UNV-MGY

EcoForm, Small, 64 LEDs, 1A, 4000K, Generation 2, Type 3, Medium Grey - 116 lm/W

In any outdoor site and area project, the next generation of Philips Gardco EcoForm LED site and area luminaires are more than sources of illumination; they offer the best of all worlds: saving energy, saving time, and saving money for significant and enduring value. It's not just about meeting technical requirements. It's about looking out for the best interests of your customers, and going the extra mile to uncover new savings and conveniences!

Product data

General Information		DesignLights Consortium Qualified Product List	
Lamp Source Code	LED	IP Rating	IP65
Color Temperature	4000K	Vibration Rating	3.0G
CRI	70	Initial Performance (IEC Compliant)	
Photometric Distribution Type	Type III	Luminaire Lumens	23900
Mounting	Pole Arm Wall	Efficacy	116 lm/W
B.U.G. Rating	B3U0G4	Application Conditions	
Awards	DLC QPL	Max Ambient Temp	+40 °C
Operating and Electrical		Min Ambient Temp	-40 °C
Voltages	120/277/UNIV V	Product Data	
Luminaire Input Watts	206	Order product name	RS-ECF-S-64L-1A-NW-G2-AR-3-UNV-MGY
Approval and Application			
Safety Listing	UL		

EcoForm LED site and area G2 - small (ECF-S)

EAN/UPC - Product	190096018192
Order code	RS-ECF-S-64L-1A-NW-G2-AR-3-UNV-MGY
Local order code	.
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401466015
Net Weight (Piece)	13.202 kg

Commercial Code	RS-ECF-S-64L-1A-NW-G2-AR-3-UNV-MGY
Catalog Number Description	EcoForm, Small, 64 LEDs, 1A, 4000K, Generation 2, Type 3, Medium Grey
Quick Ship	Spec Smart (10 Days) North America

