



LED General Purpose Floods FL

FL300-NW-G1-T-FL-8-BZ

LED, 300W, 4000K, Wide Flood Optics, Textured Dark Bronze - 113 lm/W

The Philips Keene LED Floodlights offer energy saving LED technology for long life and reduced maintenance. Versatile and stylish with five different sizes to choose from provides application flexibility for ground mount, wall mount, or pole mount installations. Ideal for sign lighting, building facades, security lighting, and general purpose floodlighting applications.

Product data

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	80
Photometric Distribution Type	NEMA 7H x 7V
Mounting	Surface Ground / Floor Wall
Operating and Electrical	
Voltages	120/208/240/277 V
Luminaire Input Watts	301
Mechanical and Housing	
Shape	Rectangular
Material	Aluminum

Approval and Application	
Safety Listing	UL
Energy Certifications	DLC Standard
DesignLights Consortium Qualified Product List	DesignLights Consortium Qualified Product List
IP Rating	IP66
Initial Performance (IEC Compliant)	
Luminaire Lumens	34025
Efficacy	113 lm/W
Product Data	
Order product name	FL300-NW-G1-T-FL-8-BZ
EAN/UPC - Product	783352024190
Order code	FL300-NW-G1-T-FL-8-BZ
Local order code	.

LED General Purpose Floods FL

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401467975
Net Weight (Piece)	17.200 kg
Commercial Code	FL300-NW-G1-T-FL-8-BZ

Catalog Number Description	LED, 300W, 4000K, Wide Flood Optics, Textured Dark Bronze
Quick Ship	Service Smart (2 Days) USA

