



LED General Purpose Floods FL

FL20-NW-G1-K-FL-6-BZ

LED, 20W, 4000K, Wide Flood Optics, Textured Dark Bronze - 109 lm/W

The Philips Keene LED Floodlights offer energy saving LED technology for long life and reduced maintenance. Versatile and stylish with five different sizes to choose from provides application flexibility for ground mount, wall mount, or pole mount installations. Ideal for sign lighting, building facades, security lighting, and general purpose floodlighting applications.

Product data

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	80
Photometric Distribution Type	NEMA 7H x 6V
Mounting	NPT/NPS Ground / Floor Wall
Operating and Electrical	
Voltages	347 V
Luminaire Input Watts	20
Mechanical and Housing	
Shape	Rectangular
Material	Aluminum

Approval and Application	
Safety Listing	UL
Energy Certifications	DLC Standard
DesignLights Consortium Qualified Product	DesignLights Consortium Qualified Product List
List	
IP Rating	IP66
Vibration Rating	1.5G
Initial Performance (IEC Compliant)	
Luminaire Lumens	2122
Efficacy	109 lm/W
Product Data	
Order product name	FL20-NW-G1-K-FL-6-BZ
EAN/UPC - Product	783352024206
Order code	FL20-NW-G1-K-FL-6-BZ

Datasheet, 2018, July 23 data subject to change

LED General Purpose Floods FL

Local order code	
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401467976
Net Weight (Piece)	2.250 kg

Commercial Code	FL20-NW-G1-K-FL-6-BZ
Catalog Number Description	LED, 20W, 4000K, Wide Flood Optics, Textured
	Dark Bronze

