



CoreLine Wall-mounted

WL130V LED12S/840 PSU WH

CoreLine Wall-mounted, 12 W, D350 mm, 1200 lm, 4000 K, IP65

CoreLine Wall-mounted is a circular-shaped surface-mounted luminaire that is easy to apply in circulation areas such as hallways and staircases. The modern unobtrusive design, in combination with its homogeneous light distribution it delivers, ensures that this luminaire blends into most building architectures. With the push-in connectors, installation is fast and straightforward

Product data

General Information			
Lamp family code	LED12 [LED Module 1200 lm]	Flammability mark	-
Light source replaceable	No	ENEC mark	ENEC mark
Number of gear units	Unit	Glow-wire test	Temperature 650 °C, duration 30 s
Driver included	Yes	EU RoHS compliant	Yes
Remarks	*- According to the Lighting Europe guidance paper 'Evaluating performance of LED based luminaires – January 2018': statistically there is no relevant difference in lumen maintenance between the B50 and, for example, the B10. Therefore, the median useful life (B50) value also represents the B10 value.		
Lighting Technology	LED	Light Technical	
Value ladder	Performance	Luminous Flux	1,200 lm
CE mark	Yes	Correlated Colour Temperature	4000 K
Warranty period	5 years	Luminous efficacy (rated) (nom.)	100 lm/W
		Colour rendering index (CRI)	80
		Beam angle of light source	120 degree(s)
		Light source colour	840 neutral white
		Optic type	Opal prismatic reflector
		Optical cover type	Opal bowl with painted cover
		Luminaire light beam spread	120°

CoreLine Wall-mounted

Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	NA W
Average CLO power consumption	NA W
End CLO power consumption	NA W
Inrush current	12.3 A
Inrush time	1.44 ms
Power Consumption	12 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 3-pole
Cable	-
Number of products on MCB of 16 A type B	32

Temperature

Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing material	Polyamide
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Housing Colour	White
Optical cover/lens finish	Opal
Overall length	350 mm
Overall width	350 mm
Overall height	70 mm
Overall diameter	350 mm
Dimensions (height x width x depth)	70 x 350 x 350 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.39, 0.39) SDCM<3
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Driver failure rate at 5,000 hours	0.7 %
Control gear failure rate at median useful life 50,000 h	5 %
Lumen maintenance at median useful life* L70	50,000 h


Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes

Product Data

Order product name	WL130V LED12S/840 PSU WH
Full product name	WL130V LED12S/840 PSU WH
Full EOC	871869938779299
Order code	38779299
Material no. (12 NC)	912401483183
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8718699387792
Numerator – packs per outer box	6
EAN/UPC – Case	8718699387976

Dimensional drawing



CoreLine Wall-mounted

