



CoreLine Wall-mounted

WL131V LED34S/830 PSU WH

CoreLine Wall-mounted, 36 W, D480 mm, 3400 lm, 3000 K, IP65

CoreLine Wall-mounted is a circular-shaped surface-mounted luminaire that is easy to apply in circulation areas such as hallways and staircases. The modern unobtrusive design, in combination with its homogeneous light distribution it delivers, ensures that this luminaire blends into most building architectures. With the push-in connectors, installation is fast and straightforward

Product data

| General Information | | | |
|--------------------------|--|----------------------------------|-----------------------------------|
| Lamp family code | LED34S [LED module, system flux 3400 lm] | Warranty period | 5 years |
| Light source replaceable | No | Flammability mark | - |
| Number of gear units | Unit | ENEC mark | ENEC mark |
| Driver included | Yes | Glow-wire test | Temperature 650 °C, duration 30 s |
| Remarks | *- According to the Lighting Europe guidance paper 'Evaluating performance of LED based luminaires – January 2018': statistically there is no relevant difference in lumen maintenance between the B50 and, for example, the B10. Therefore, the median useful life (B50) value also represents the B10 value. | EU RoHS compliant | Yes |
| Lighting Technology | | Light Technical | |
| Lighting Technology | LED | Luminous Flux | 3,400 lm |
| Value ladder | Performance | Correlated Colour Temperature | 3000 K |
| CE mark | Yes | Luminous efficacy (rated) (nom.) | 95 lm/W |
| | | Colour rendering index (CRI) | 80 |
| | | Beam angle of light source | 120 degree(s) |
| | | Light source colour | 830 warm white |
| | | Optic type | Opal prismatic reflector |
| | | Optical cover type | Opal bowl with painted cover |

CoreLine Wall-mounted

| | |
|-----------------------------|------|
| Luminaire light beam spread | 120° |
|-----------------------------|------|

Operating and Electrical

| | |
|--|--------------------------|
| Input Voltage | 220-240 V |
| Line Frequency | 50 to 60 Hz |
| Initial CLO power consumption | NA W |
| Average CLO power consumption | NA W |
| End CLO power consumption | NA W |
| Inrush current | 13.5 A |
| Inrush time | 1.75 ms |
| Power Consumption | 36 W |
| Power Factor (Fraction) | 0.9 |
| Connection | Push-in connector 3-pole |
| Cable | - |
| Number of products on MCB of 16 A type B | 32 |

Temperature

| | |
|---------------------------|---------------|
| Ambient temperature range | -20 to +40 °C |
|---------------------------|---------------|


Controls and Dimming

| | |
|-------------------------------|----------------------------|
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Constant light output | No |

Mechanical and Housing

| | |
|-----------------------------|---------------|
| Housing material | Polyamide |
| Reflector material | - |
| Optic material | Polycarbonate |
| Optical cover/lens material | Polycarbonate |
| Fixation material | - |
| Housing Colour | White |
| Optical cover/lens finish | Opal |
| Overall length | 480 mm |
| Overall width | 480 mm |
| Overall height | 70 mm |
| Overall diameter | 480 mm |

Dimensional drawing



| | |
|-------------------------------------|-------------------|
| Dimensions (height x width x depth) | 70 x 480 x 480 mm |
|-------------------------------------|-------------------|

Approval and Application

| | |
|------------------------------|--|
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK08 [5 J vandal-protected] |
| Protection class IEC | Safety class II |

Initial Performance (IEC Compliant)

| | |
|-----------------------------|---------------------|
| Luminous flux tolerance | +/-10% |
| Initial chromaticity | (0.44, 0.41) SDCM<3 |
| Power consumption tolerance | +/-10% |

Over Time Performance (IEC Compliant)

| | |
|--|-------|
| Driver failure rate at 5,000 hours | 0.7 % |
| Control gear failure rate at median useful life 50,000 h | 5 % |
| Lumen maintenance at median useful life* 50,000 h | L70 |

Application Conditions

| | |
|------------------------------------|----------------|
| Performance ambient temperature Tq | 25 °C |
| Maximum dim level | Not applicable |
| Suitable for random switching | Yes |

Product Data

| | |
|-----------------------------------|--------------------------|
| Order product name | WL131V LED34S/830 PSU WH |
| Full product name | WL131V LED34S/830 PSU WH |
| Full EOC | 871869938784699 |
| Order code | 38784699 |
| Material no. (12 NC) | 912401483188 |
| SAP numerator – quantity per pack | 1 |
| EAN/UPC – Product/Case | 8718699387846 |
| Numerator – packs per outer box | 6 |
| EAN/UPC – Case | 8718699388027 |

CoreLine Wall-mounted

