



Gear for SDW-T lamps

CSLS 100 SDW-T 220-240V 50/60Hz

CSLS electronic control unit with impregnated (HID 'BASIC') or encapsulated (HID 'Heavy Duty') electromagnetic ballasts

Warnings and Safety

- Climatic suitability CSLS and HID BASIC: restricted to built in situations under normal conditions
- Climatic suitability CSLS and HID Heavy Duty: use in luminaires under humid conditions (not drip-proof)

Product data


| General Information | |
|---|---------------------------|
| Lamp type | SDW-T |
| Number of lamps | 1 piece/unit |
| Operating and Electrical | |
| Input Voltage | 220 to 240 V |
| Input frequency | 50 to 60 Hz |
| Response voltage | 210 V |
| Mains voltage performance (AC) | -4%~+9% |
| Mains voltage safety (AC) | -10%~+10% |
| Output peak voltage (max.) | 4500 V |
| Power losses (nom.) | 4.0 W |
| Wiring | |
| Cable length from device to lamp | 0.50 m |
| Wire strip length | 6.0 mm |
| Ballast contact wire cross section | 0.50-2.50 mm ² |
| Cable capacity output wires to earth (nom.) | 50 pF |
| Connector type | Screw |

| System characteristics | |
|-----------------------------------|---|
| Rated ballast-lamp power | 100 W |
| Temperature | |
| T-ambient (max.) | 65 °C |
| T storage (max.) | 80 °C |
| T storage (min.) | -25 °C |
| T-case lifetime (nom.) | 90 °C |
| T-Case maximum (max.) | 90 °C |
| Approval and Application | |
| Vibration standard | IEC68-2-6 F c |
| Approval marks | CE marking VDE-EMV certificate CB Certificate |
| Product Data | |
| Full product code | 871150090870430 |
| Order product name | CSLS 100 SDW-T 220-240V 50/60Hz |
| EAN/UPC – product | 8711500908704 |
| Order code | 90870430 |
| SAP numerator – quantity per pack | 1 |

Gear for SDW-T lamps

| | |
|---------------------------------|--------------|
| Numerator – packs per outer box | 18 |
| SAP material | 913619189966 |
| SAP net weight (piece) | 0.259 kg |

Dimensional drawing



CSLS 100 SDW-T 220-240V 50/60Hz

Product

CSLS 100 SDW-T 220-240V 50/60Hz

