



Core & Coil (71A) LPS

CORE & COIL HID LPS BAL 35/55W L70/71 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	L71
Lamp Type	55W LPS
Number of Lamps	1 piece/unit
Circuit Type	HX-HPF
Ballast Type	Magnetic HID
Base Model	71A0490
Core Size	3 X 4 (2 coil)
Suitable For Outdoor Use	Yes
Capacitor Value	14 MFD
Capacitor Catalog Number	7C140M30RA
Capacitor Requirements	240V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval	1.65 in
Dimensions	
Capacitor Height	2.75 in
Automatic Restart	No
	·
Operating and Electrical	
Input Voltage	120/208/240/277 V
Input Frequency	60 Hz
Inp. Current (Open Circuit)	2.35/1.39/1.18/0.98 A
Input Current (Starting)	0.8/0.46/0.39/0.36 A

Input Current (Short Circuit)	0.36-0.54/0.23-0.34/0.2-0.3/0.16-0.25 A
Secondary Short Circuit Current	0.5-0.7 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	480 V
Input Current (Operating) (Nom)	0.73/0.42/0.36/0.32 A A
Input Power (Nom)	80 W
Rated Lamp Watts	55 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration	Yes
Allowed	
Max Ballast-Lamp Distance	Determined by AWG used
Remote Wiring	
Recommended Fuse Value	6/4/3/3 A
Approval and Application	
Open Circuit Voltage Test (Volts)	430-530 V
Approbation Marks	ULR CSA certificate RoHS Compliant

Datasheet, 2019, February 12 data subject to change


Core & Coil (71A) LPS

	0 / 0 / 0 / 0
Temperature Marking	A/A/A/A
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029A

EAN/UPC - Product	781087119990
Order code	71A0490500D
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913700502041
Net Weight (Piece)	3.071 kg

Product Data	
Order product name	CORE & COIL HID LPS BAL 35/55W L70/71 QUAD
	C&C

Dimensional drawing



LPS BAL 35/55W L70/71 QUAD C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A0490500D	3.5 in	2.25 in	3.9 in	3.5 in	2.8 in	2.4 in

