



Core & Coil (71A) MH ~LT~ 175W

CORE & COIL HID MH BAL 70W M98/143 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information					
ANSI Code	M98-M143				
Lamp Type	70W MH				
Number of Lamps	1 piece/unit				
Circuit Type	HX-HPF				
Ballast Type	Magnetic HID				
Base Model	71A5292				
Core Size	3 X 4 (2 LW)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	LI533-H4				
Ignitor Temperature Rating	105°C				
Capacitor Value	8 MFD				
Capacitor Catalog Number	7C080L30RA				
Capacitor Requirements	280V				
Capacitor Temperature Rating	105°C				
Capacitor Diameter/Oval	1.25 in				
Dimensions					
Capacitor Height	2.75 in				
Automatic Restart	No				

Operating and Electrical				
Input Voltage	120/208/240/277 V			
Input Frequency	60 Hz			
Input Current (Open Circuit)	1.66/0.97/0.83/0.73 A			
Input Current (Starting)	0.71/0.41/0.4/0.3 A			
Input Current (Short Circuit)	0.65-0.98/0.4-0.6/0.32-0.49/0.29-0.44 A			
Secondary Short Circuit Current	1.03-1.26 A			
Constant Wattage Deviation	7%			
Ballast Factor (Nom)	1			
Power Factor (Nom)	0.90			
Open Circuit Voltage	255 V			
Input Current (Nom)	0.85/0.49/0.42/0.37 A A			
Input Power (Nom)	92 W			
Rated Lamp Power	70 W			
Wiring				
Wire Striplength	0.5 mm			
Wire Length by Color	12"			
Wire Type	Stranded			


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) MH ~LT~ 175W

Remote Wiring Configuration	Yes				
Allowed					
Max Ballast-Lamp Distance	15'				
Remote Wiring					
Recommended Fuse Value	4/3/2/2 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	230-280 V				
Approval Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	A/A/A/A				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				

UL Temperature Code	1029A
Product Data	
Order product name	CORE & COIL HID MH BAL 70W M98/143 QUAD C&C
EAN/UPC - Product	781087017296
Order code	177527
Local order code	177527
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913700502591
Net Weight (Piece)	2.391 kg
	·

Dimensional drawing



MH BAL 70W M98/143 QUAD C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5292510D	2.88 in	1.44 in	3.9 in	3.5 in	2.8 in	2.4 in

