



# Core & Coil (71A) HPS ~LT~ 200W

## CORE & COIL HID HPS BAL 50W S68 120/277V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information				
ANSI Code	S68			
Lamp Type	50W HPS			
Number of Lamps	1 piece/unit			
Circuit Type	HX-HPF			
Ballast Type	Magnetic HID			
Base Model	71A7801			
Core Size	3 X 4 (2 coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI551-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	5 MFD			
Capacitor Catalog Number	7C050L30RA			
Capacitor Requirements	280V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.25 in			
Capacitor Height	2.25 in			
Automatic Restart	No			

Operating and Electrical					
Input Voltage	120/277 V				
Input Frequency	60 Hz				
Inp. Current (Open Circuit)	1/0.45 A				
Input Current (Starting)	0.65/0.3 A				
Input Current (Short Circuit)	0.6-0.8/0.25-0.35 A				
Secondary Short Circuit Current	1.3-1.9 A				
Constant Wattage Deviation	Within Trapezoid				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Nominal Open Circuit Voltage	125 V				
Input Current (Operating) (Nom)	0.61/0.26 A A				
Input Power (Nom)	66 W				
Rated Lamp Watts	50 W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length by Color	12"				
Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				


Datasheet, 2019, February 12 data subject to change

### Core & Coil (71A) HPS ~LT~ 200W

Max Ballast-Lamp Distance Remote Wiring	2'			
Recommended Fuse Value	3/1 A			
Approval and Application				
Open Circuit Voltage Test (Volts)	115-135 V			
Approbation Marks	ULR CSA certificate RoHS Compliant			
Temperature Marking	A/A			
UL Recognized	Yes			
Hipot Test (1 Minute)	2000 V			
Hipot Test (2 Seconds)	2500 V			
UL Insulation Class	H(180°C)			
UL Temperature Code	1029A			

Product Data			
Order product name	CORE & COIL HID 71A7801510D		
EAN/UPC - Product	781087023594		
Order code	71A7801510D		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	6		
Material Nr. (12NC)	913700504431		
Net Weight (Piece)	1.765 kg		

#### Dimensional drawing



HPS BAL 50W S68 120/277V KIT

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A7801510D	2.2 in	1 in	3.9 in	3.5 in	2.8 in	2.4 in

