



# **SmartMate**

# SMARTMATE ELE BALLAST (2) 26W CFL (4-PIN) 120-277V

Offering maximum versatility, the Philips Advance family of SmartMate ballasts for 4-pin compact fluorescent lamps drive a broad range of quad and triple-tube, circline, 2D, and long twin-tube lamps. SmartMate ballasts' energy efficient design, compact and lightweight housing, and user-friendly features make these ballasts an ideal choice for fixture manufacturers, retrofitters, and MRO replacement.

#### **Product data**

General Information					
Lamp Type	CFQ26W/G24Q				
Number of Lamps	1/2 piece/unit				
Ballast Type	Electronic Fluorescent				
Base Model	ICF2S26M1BS				
Suitable For Outdoor Use	Yes				
Automatic Restart	Yes				
Operating and Electrical					
Input Voltage	120 to 277 V				
Input Frequency	50 to 60 Hz				
Total Harmonic Distortion USA	10 %				
Ignition Method	Programmed Start				
Crestfactor (Nom)	1.5				
Ignition Time (Nom)	1.5 s				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.98				
Input Current (Max)	0.43 A				
Input Current (Min)	0.19 A				
Input Power (Nom)	51-51 W				

Rated Lamp Power	26 W
Wiring	
Color Input Terminals	Black and White
Color Output Terminals	RED, YEL & BLU
Wire Striplength	0.375 mm
Lamp Connection	Series
Wire Length by Color	No wires
Wire Gauge (Nom)	18AWG mm
Wire Type	Solid
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	Yes
Through Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	1-L = 15' / 2-L = 6'
Max Ballast-Lamp Distance Tandem Wiring	2-L: Red = 6'
Max Ballast-Lamp Distance Through Wiring	2-L: Red = 6'
Connector Type	Poke-In
Temperature	
T-Case Maximum (Nom)	75 ℃


Datasheet, 2019, February 12 data subject to change

## **SmartMate**

Mechanical and Housing	
Housing Material	Metal
Housing	M1
Housing Dimensions	4.98" x 2.4" x 0.98"
Approval and Application	
EMC Immunity Standard	FCC Non-Consumer
Approval Marks	CSA certificate UL certificate CEC Listing
	RoHS Compliant
Hum And Noise Level	A
UL Recognized	No

Product Data			
Order product name	SMARTMATE ELE BALLAST (2) 26W CFL		
	(4-PIN) 120-277V		
EAN/UPC - Product	781087104064		
Order code	913700532409		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	840		
Material Nr. (12NC)	913700532409		
Net Weight (Piece)	204.000 g		

## Dimensional drawing



SMARTMATE ICF2S26M1BS35B

Product	A1	A2	А3	B1	C1
SMARTMATE ELE BALLAST (2) 26W	4.60 in	4.20 in	2.00 in	2.40 in	0.98 in
CFL (4-PIN) 120-277V					

