**PHILIPS** Lighting



# Core & Coil (71A) MH ~LT~ 175W

# CORE & COIL HID MH BAL 100W M90/140 277V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information	
ANSI Code	M90-M140
Lamp Type	100W MH
Number of Lamps	1 piece/unit
Circuit Type	R-HPF
Ballast Type	Magnetic HID
Base Model	71A5337P
Core Size	2 5/8 x 2 3/16
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI533-H4
Ignitor Temperature Rating	105°C
Capacitor Value	10 MFD
Capacitor Catalog Number	7C100M30RA
Capacitor Requirements	280V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.65 in
Capacitor Height	2.75 in
Automatic Restart	No


Operating and Electrical	
Input Voltage	277 V
Input Frequency	60 Hz
Inp. Current (Open Circuit)	1.05 A
Input Current (Starting)	0.7 A
Input Current (Short Circuit)	0.25-0.35 A
Secondary Short Circuit Current	1.05-1.55 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	277 V
Input Current (Operating) (Nom)	0.45 A A
Input Power (Nom)	118 W
Rated Lamp Watts	100 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes

### Core & Coil (71A) MH ~LT~ 175W


Max Ballast-Lamp Distance Remote Wiring 2'		
Recommended Fuse Value	3 A	
Approval and Application		
Open Circuit Voltage Test (Volts)	260-290 V	
Approbation Marks	ULR CSA certificate RoHS Compliant	
Temperature Marking	А	
UL Recognized	Yes	
Hipot Test (1 Minute)	2000 V	
Hipot Test (2 Seconds)	2500 V	
UL Insulation Class	H(180°C)	
UL Temperature Code	1029A	

Product Data	
Order product name	CORE & COIL HID MH BAL 100W M90/140
	277V C&C
EAN/UPC - Product	781087097618
Order code	71A5337500DP
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913700532609
Net Weight (Piece)	1.348 kg

### **Dimensional drawing**



MH BAL 100W M90/140 127/220V C&C





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, February 12 - data subject to change