



# Encapsulated Core & Coil (73B)

## ENCAPSULATED CORE & COIL HID MH BAL 175W M57 QUAD ENCAP

Where quiet performance is required, the standard open core and coil ballast is encapsulated (potted) in a cube-shaped steel can utilizing Class H (180°C) polyester compound.

#### **Product data**

General Information							
ANSI Code	M57-M107						
Lamp Type	175/150W MH						
Number of Lamps	1 piece/unit						
Circuit Type	CWA						
Ballast Type	Magnetic HID						
Base Model	73B5590						
Suitable For Outdoor Use	Yes						
Ignitor Catalog Number	NA						
Ignitor Temperature Rating	NA						
Capacitor Value	10 MFD						
Capacitor Catalog Number	7C100M40R						
Capacitor Requirements	400V						
Capacitor Temperature Rating	105°C 1.45 in						
Capacitor Diameter/Oval Dimensions							
Capacitor Height	3.75 in						
Automatic Restart	No						
Operating and Electrical							
Input Voltage	120/208/240/277 V						

Input Frequency	60 Hz						
Input Current (Open Circuit)	1.8/1.04/0.9/0.8 A 1.3/0.75/0.65/0.55 A 0.8-1.2/0.45-0.7/0.4-0.6/0.3-0.5 A 1.5-1.9 A						
Input Current (Starting)							
Input Current (Short Circuit)							
Secondary Short Circuit Current							
Constant Wattage Deviation	10%						
Ballast Factor (Nom)	1						
Power Factor (Nom)	0.90						
Open Circuit Voltage	305 V						
Input Current (Nom)	1.8/1.04/0.9/0.8 A A						
Input Power (Nom)	210 W						
Rated Lamp Power	175/150 W						
Wiring							
Wire Striplength	0.5 mm						
Wire Length by Color	12"						
Wire Type	Stranded						
Remote Wiring Configuration Allowed	Yes						
Max Ballast-Lamp Distance Remote	Determined by AWG used						
Wiring							

### Encapsulated Core & Coil (73B)

Recommended Fuse Value	5/3/3/2 A				
Mechanical and Housing					
Housing Material	Metal				
Housing	Encap				
Housing Dimensions	4.6" x 4.4" x 3.6"				
Approval and Application					
Open Circuit Voltage Test (Volts)	275-335 V				
Approval Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	C/D/D/D				
Hum And Noise Level	A				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	25000 V				

H(180°C)				
1029D				
ENCAPSULATED CORE & COIL HID MH BAL				
175W M57 QUAD ENCAP				
781087100448				
193771				
193771				
1				

4

913700542909

4.605 kg


Numerator - Packs per outer box

Material Nr. (12NC)

Net Weight (Piece)

Duralizat

#### **Dimensional drawing**



Product	AI	AZ	A3	ы	BZ	CI	וט	
ENCAPSULATED CORE & COIL HID	6 in	5.25 in	4.6 in	3.6 in	2 in	4.4 in	0.25 in	
73B5590500D								

41 40

A2 01 02 C1

- -

MH BAL 175W M57 QUAD ENCAP



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, March 8 - data subject to change