



Core & Coil (71A) HPS ~GT~ 400W

CORE & COIL HID HPS BAL 1000W S52 480V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

| General Information | |
|------------------------------------|--------------|
| ANSI Code | S52 |
| Lamp Type | 1000W HPS |
| Number of Lamps | 1 piece/unit |
| Circuit Type | CWA |
| Ballast Type | Magnetic HID |
| Base Model | 71A8743 |
| Core Size | 4 1/4 x 6 |
| Suitable For Outdoor Use | Yes |
| Ignitor Catalog Number | LI571-H5 |
| Ignitor Temperature Rating | 105°C |
| Capacitor Value | 26 MFD |
| Capacitor Catalog Number | RW1626020 |
| Capacitor Requirements | 525V |
| Capacitor Temperature Rating | 90℃ |
| Capacitor Diameter/Oval Dimensions | 1.75 in |
| Capacitor Height | 4.25 in |
| Automatic Restart | No |
| | |
| Operating and Electrical | |
| Input Voltage | 480 V |
| | |

| Input Frequency | 60 Hz | |
|---|------------------|--|
| Inp. Current (Open Circuit) | 0.9 A | |
| Input Current (Starting) | 1.6 A | |
| Input Current (Short Circuit) | 1.75-2.65 A | |
| Secondary Short Circuit Current | 6.4-7.8 A | |
| Constant Wattage Deviation | Within Trapezoid | |
| Ballast Factor (Nom) | 1 | |
| Power Factor (Nom) | 0.90 | |
| Nominal Open Circuit Voltage | 435 V | |
| Input Current (Operating) (Nom) | 2.3 A A | |
| Input Power (Nom) | 1100 W | |
| Rated Lamp Watts | 1000 W | |
| | | |
| Wiring | | |
| Wire Striplength | 0.5 mm | |
| Wire Length by Color | 12" | |
| Wire Type | Stranded | |
| Remote Wiring Configuration Allowed | Yes | |
| Max Ballast-Lamp Distance Remote Wiring 15' | | |
| Recommended Fuse Value | 6 A | |
| | | |


Datasheet, 2019, March 22 data subject to change

Core & Coil (71A) HPS ~GT~ 400W

| Approval and Application | |
|-----------------------------------|------------------------------------|
| Open Circuit Voltage Test (Volts) | 395-485 V |
| Approbation Marks | ULR CSA certificate RoHS Compliant |
| Temperature Marking | С |
| UL Recognized | Yes |
| Hipot Test (1 Minute) | 2000 V |
| Hipot Test (2 Seconds) | 2500 V |
| UL Insulation Class | H(180°C) |
| UL Temperature Code | 1029C |
| | |
| Product Data | |
| Order product name | CORE & COIL HID HPS BAL 1000W S52 |
| | 480V C&C |

| EAN/UPC - Product | 781087874356 |
|---------------------------------|--------------|
| Order code | 71A8743500 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 2 |
| Material Nr. (12NC) | 913700566109 |
| Net Weight (Piece) | 13.313 kg |
| | |

Dimensional drawing



HPS BAL 1000W S52 480V C&C

 Product
 C1
 C2
 A1
 A2
 A3
 B1
 B2

 CORE & COIL HID HPS BAL 1000W
 5.90 in
 3.90 in
 6 in
 5.4 in
 4.4 in
 4.3 in
 3.9 in

 S52 480V C&C

