



# HF-Performer II for PL-T/C/R/L/TL5C lamps

## HF-P 1 13-17 PL-T/C/R EII 220-240V

Compact, lightweight high-frequency electronic ballast for PL-T/C/TL5C/R/L fluorescent lamps, based on EII technology

### Product data


Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Inrush Current Width	0.25 ms
Inrush Current Peak (Max)	18 A
Number of Products on MCB (16A Type B) (Nom)	28
Wiring	
Connector Type Input Terminals	Insert
Connector Type Output Terminals	Insert
Temperature	
Ambient temperature range	-25 °C to 50 °C
T-Case Lifetime (Nom)	75 °C
T-Case Maximum (Max)	75 °C
Approval and Application	
Ingress protection code	IP20 [Finger-protected]

Energy Efficiency Index	A2
Safety Standard	IEC 61347-2-3
Environmental Standard	ISO 14001
Approval Marks	CE marking ENEC certificate VDE-EMV certificate

Product Data	
Order product name	HF-P 1 13-17 PL-T/C/R EII 220-240V
Full product name	HF-P 1 13-17 PL-T/C/R EII 220-240V
Full product code	871150091407130
Order code	91407130
Material Nr. (12NC)	913700631166
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500914071
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500914088

HF-Performer II for PL-T/C/R/L/TL5C lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1	B2
HF-P 113-17 PL-T/C/R/L/TL5C EII 220-240V	4.5 mm	30.0 mm	103.0 mm	93.5 mm	67.0 mm	57.5 mm

