

AspiraVision Compact for CDM

HID-AV C 70 /C CDM 220-240V 50/60Hz


AspiraVision is the mark of excellence in HID electronic gear technology – high-end, compact, lightweight and easy to use, with added features for optimal performance of 35, 50 and 70 W CDM lamps. The recently added switching function provides maximum flexibility for users by integrating three different wattage choices into a single driver.

Product data

Operating and Electrical		Controls and Dimming	
Input Voltage	220 to 240 V	Control Interface	-
Line Frequency	50 to 60 Hz		
Input Frequency	50 to 60 Hz	Mechanical and Housing	
Earth Leakage Current (Max)	250 mA	Housing	/C
Inrush Current Width	10 ms		
Input Current (Nom)	0.45 A	Approval and Application	
Inrush Current Peak (Max)	8 A	Approval Marks	F-Marking CE marking ENEC certificate VDE certificate CB Certificate VDE-EMC marking
Number of Products on MCB (16A Type B) (Nom)	32		
Wiring		Product Data	
Cable Length From Device to Lamp	2 m	Order product name	HID-AV C 70 /C CDM 220-240V 50/60Hz
Connector Type	Wieland	Full product name	HID-AV C 70 /C CDM 220-240V 50/60Hz
Temperature		Full product code	872790088523100
Ambient temperature range	-20 °C to 55 °C	Order code	913700646966
T-Case Lifetime (Nom)	80 °C	Material Nr. (12NC)	913700646966
		Numerator - Quantity Per Pack	1
		EAN/UPC - Product/Case	8711500881656
		Numerator - Packs per outer box	12
		EAN/UPC - Case	8727900885231

AspiraVision Compact for CDM

Dimensional drawing



Product	D1	C1	A1	A2	B1
HID-AV C 70 /C CDM 220-240V 50/60Hz	4.8 mm	32.4 mm	162.2 mm	143 mm	83.0 mm

