



# HID ignitors for MK4 semi-parallel systems

## SKD 578-S 220-240V 50/60Hz

HID ignitors for semi-parallel systems


#### **Product data**

Operating and Electrical		
Input Voltage	220 to 240 V	
Line Frequency	50 to 60 Hz	
Input Frequency	50 to 60 Hz	
Wiring		
Connector Type	Screw	
Temperature		
Ambient temperature range	-30 °C to 85 °C	
T-Case Maximum (Max)	90 ℃	
Approval and Application		
Approval Marks	CE marking ENEC certificate	

Product Data			
Order product name	SKD 578-S 220-240V 50/60Hz		
Full product name	SKD 578-S 220-240V 50/60Hz		
Full product code	872790089569800		
Order code	89569800		
Material Nr. (12NC)	913700655466		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8711500881779		
Numerator - Packs per outer box	20		
EAN/UPC - Case	8727900895698		

### HID ignitors for MK4 semi-parallel systems

#### Dimensional drawing



Product	A1	B1	C1
SKD 578-S 220-240V 50/60Hz	67.5 mm	40.5 mm	28.0 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 15 - data subject to change