



# PrimaVision Compact for CDM

## HID-PV C 35 /G CDM 220-240V 50/60Hz

High-quality, compact and lightweight HID electronic gear for optimal and reliable performance of 20, 35, 50 and 70 W CDM lamps

### Product data

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Earth Leakage Current (Max)	0.25 mA
Inrush Current Width	0.25 ms
Inrush Current Peak (Max)	26 A
Number of Products on MCB (16A Type B) (Nom)	24
Wiring	
Cable Length From Device to Lamp	2.0 m
Connector Type	Wieland
Temperature	
Ambient temperature range	-20 °C to 50 °C
T-Case Lifetime (Nom)	75 °C
T-Case Maximum (Max)	75 °C
Mechanical and Housing	
Housing	/G

Approval and Application	
Safety Standard	EN 61347-2-12
Environmental Standard	ISO 14001
Approval Marks	CE marking ENEC certificate
Product Data	
Order product name	HID-PV C 35 /G CDM 220-240V 50/60Hz
Full product name	HID-PV C 35 /G CDM 220-240V 50/60Hz
Full product code	872790091642300
Order code	913700662495
Material Nr. (12NC)	913700662495
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900916423
Numerator - Packs per outer box	6
EAN/UPC - Case	8727900916430

PrimaVision Compact for CDM

Dimensional drawing

Product	D1	C1	A1	A2	B1
HID-PV C 35 /G CDM 220-240V 50/60Hz	4.8 mm	34.5 mm	188.0 mm	170.0 mm	82.7 mm

