


AspiraVision Compact for CDM

HID-AV C 35-70 /S CDM 220-240V 50/60Hz

AspiraVision is the mark of excellence in HID electronic gear technology – high-end, compact, lightweight and easy to use, with added features for optimal performance of 35, 50 and 70 W CDM lamps.。The recently added switching function provides maximum flexibility for users by integrating three different wattage choices into a single driver.

产品数据

操作和电气	
输入电压	220 至 240 V
线频率	50 to 60 Hz
输入频率	50 至 60 Hz
对地漏电流 (最大)	0.25 mA
侵入电流宽度	10 ms
侵入电流峰值 (最大)	8 A
MCB 上的产品数量 (16A 类型 B)(标称)	58

布线	
从设备到灯具的电缆长度	2 m
连接器类型	WAGO 804 系列

温度	
环境温度范围	-20 °C 至 55 °C
外壳温度使用寿命 (标称)	80 °C

控制和调光	
控制接口	-


机械和外壳	
外壳	/S

审批和申请	
浪涌保护 (通用/差异)	EN61547 (L-L 2kV , L-G 4kV) kV
安全标准	EN 61347-2-12 和 2-1
环保标准	ISO 14001
批准标志	F 标记 CE 标记 ENEC 证书 VDE 证书 CB 证书 VDE-EMC 标记

产品数据	
订单产品名称	HID-AV C 35-70 /S CDM 220-240V 50/60Hz
完整的产品名称	HID-AV C 35-70 /S CDM 220-240V 50/60Hz
完整产品代码	871829123310700
订购代码	913700683866
材料编号 (12NC)	913700683866
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8718291233107
计算器 - 每个外包装箱中的包数	12
EAN/UPC - 案例	8718291233114

AspiraVision Compact for CDM

二维绘图



Product	D1	C1	A1	A2	B1	B2
HID-AV C 35-70 /S CDM 220-240V 50/60Hz	4.5 mm	32.1 mm	110.0 mm	98.5 mm	75.0 mm	63.5 mm

© 2023 Signify Holding 保留所有权利。 Signify 对此文档所包含信息的准确性或完整性不作任何陈述或保证，也不对根据此文档信息做出的任何行为负责。 本文档中提供的信息不作为任何商业要约，也不构成任何报价或合同的一部分，除非 Signify 同意。 Philips 和 Philips Shield Emblem 是 Koninklijke Philips N.V. 的注册商标。