



HF-Regulator Intelligent Touch DALI for PL-T/C and TL5C

HF-Ri TD 1 26-42 PL-T/C E+

Intelligent high-frequency electronic dimming ballast, using DALI (Digital Addressable Lighting Interface according to IEC62386) or Touch and Dim push-button protocol for fluorescent lamps. Features Corridor Mode, programmable with Philips MultiOne. High-frequency operation improves light quality and lamp lifetime. Pre-empts upcoming legislation as it meets A1BAT requirements.

Product data


Operating and Electrical		T-Case Maximum (Max)	75 °C
Input Voltage	195-240 V		
Line Frequency	50 to 60 Hz		
Input Frequency	50 to 60 Hz		
Earth Leakage Current (Max)	0.5 mA		
Inrush Current Width	0.35 ms		
Inrush Current Peak (Max)	27 A		
Number of Products on MCB (16A Type B) (Nom)	28		
Wiring		Controls and Dimming	
Connector Type Input Terminals	WAGO 250 series	Control Interface	TD
Connector Type Output Terminals	WAGO 250 series		
Temperature		Mechanical and Housing	
Ambient temperature range	-25 °C to 50 °C	Housing	L 123x79x33
T-Case Lifetime (Max)	75 °C		
		Approval and Application	
		Ingress protection code	IP20 [Finger-protected]
		Energy Efficiency Index	A1 BAT
		Safety Standard	IEC 61347-2-3
		Environmental Standard	ISO 14001
		Approval Marks	EMC CE marking ENEC certificate CCC certificate

HF-Regulator Intelligent Touch DALI for PL-T/C and TL5C

Product Data	
Order product name	HF-Ri TD 1 26-42 PL-T/C E+
Full product name	HF-Ri TD 1 26-42 PL-T/C E+
Full product code	871829124167600
Order code	913700684766
Material Nr. (12NC)	913700684766

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291241676
Numerator - Packs per outer box	12
EAN/UPC - Case	8718291241683

Dimensional drawing



Product	D1	C1	A1	A2	B1	B2
HF-Ri TD 1 26-42 PL-T/C E	4.5 mm	33.0 mm	123.0 mm	111.0 mm	79.0 mm	67.0 mm
+						

