



Core & Coil (71A) HPS ~LT~ 200W

CORE & COIL HID HPS BAL 70W (EURO LAMP) 220/240V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information				
ANSI Code	SON-TPIA			
Lamp Type	70W HPS			
Number of Lamps	1 piece/unit			
Circuit Type	LEAD-REACTOR			
Ballast Type	Magnetic HID			
Base Model	71A9916			
Core Size	2 5/8 x 2 3/16			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI501-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	10 MFD			
Capacitor Catalog Number	7C100M30RA			
Capacitor Requirements	300V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.65 in			
Capacitor Height	2.75 in			
Automatic Restart	No			

Operating and Electrical					
Input Voltage	220/240 V				
Input Frequency	60 Hz				
Inp. Current (Open Circuit)	0.83/0.9 A				
Input Current (Starting)	0.33/0.24 A				
Input Current (Short Circuit)	0.25-0.38/0.17-0.25 A				
Secondary Short Circuit Current	0.88-1.36 A				
Constant Wattage Deviation	10%				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Nominal Open Circuit Voltage	220 V				
Input Current (Operating) (Nom)	0.38/0.35 A A				
Input Power (Nom)	82 W				
Rated Lamp Watts	70 W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length by Color	12"				
Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) HPS ~LT~ 200W

Max Ballast-Lamp Distance Remote W	firing 2'
Recommended Fuse Value	2/2 A
Approval and Application	
Open Circuit Voltage Test (Volts)	202-233 V
Approbation Marks	NOM certificate RoHS Compliant
Temperature Marking	A/A
UL Recognized	No
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029A

Product Data			
Order product name	CORE & COIL HID HPS BAL 70W (EURO		
	LAMP) 220/240V C&C		
EAN/UPC - Product	781087108987		
Order code	71A9916500DML		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	4		
Material Nr. (12NC)	913701147402		
Net Weight (Piece)	1.121 kg		

Dimensional drawing



HPS BAL 70W (EURO LAMP) 220/240V C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A9916500DML	3 in	1.64 in	2.6 in	2.2 in	2.2 in	1.8 in

