PHILIPS Lighting



Micropower Electronic ballast for TL/PL-S/-T/-C lamps (India)

EBS 118 230 SH

Compact, lightweight, high-frequency electronic ballast designed for TL (6-18 W) and compact fluorescent PL (7-24 W) lamps


Product data

Operating and Electrical				
Input Voltage	220 to 240 V			
Line Frequency	50 to 60 Hz			
Input Frequency	50 to 60 Hz			
Wiring				
Connector Type Input Terminals	WAGO 251 universal connector [Suitable for both			
	automatic wiring (ALF and ADS) and manual wiring]			
Connector Type Output Terminals	WAGO 251 universal connector [Suitable for both			
	automatic wiring (ALF and ADS) and manual wiring]			
Temperature				
Ambient temperature range	0 °C to 40 °C			
T-Case Maximum (Max)	75 ℃			

Product Data		
Order product name	EBS 118 230 SH	
Full product name	EBS 118 230 SH	
Full product code	871150088497800	
Order code	913702243112	
Material Nr. (12NC)	913702243112	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8711500884978	
Numerator - Packs per outer box	50	
EAN/UPC - Case	8727900067996	

Micropower Electronic ballast for TL/PL-S/-T/-C lamps (India)

Dimensional drawing



Product	D1	C1	A1	A2	B1
EBS 118 230 SH	4.0 mm	22.0 mm	80.0 mm	65.0 mm	40.0 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 15 - data subject to change