PHILIPS

Lighting



Dynalite Integration Devices

DDNI485

Within any modern project, many third-party systems can be found performing different roles. Each separate system may use a different protocol for communication. Philips Dynalite has developed a range of gateway devices that can be used to synchronize these systems' functions into one integrated system solution. By utilizing the correct gateway, different systems can be integrated, allowing end-users access to a fully automated site from one interface. By successfully integrating third-party systems with a Dynalite solution, repetitive end-user interaction is reduced.

Product data

General Information	
Remarks	Please download the Lighting - Product Data Sheet for more information and ordering options
CE mark	CE mark
EU RoHS compliant	Yes


Temperature	
Ambient temperature range	0 to +50 °C


Approval and Application	
Ingress protection code	IP20 [Finger-protected]

Product Data	
Order product name	DDNI485
Full product name	DDNI485
Full product code	871016350788000
Order code	913703081309
Material Nr. (12NC)	913703081309
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163507880
Numerator - Packs per outer box	1
EAN/UPC - Case	8710163507897

Dynalite Integration Devices

Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.