



Dynalite Sensors

DUS360CR-DALI

The Philips Dynalite sensor range combines motion detection, light level detection and IR receive in one unit. Each of these features can be operated at the same time, allowing automation scenarios such as turning on the lights after detecting motion and then dimming the lighting level once the available sunlight has been measured, thereby providing additional energy savings. By combining each of these functions into one device, operational efficiency is improved. Each sensor has an in-built microprocessor, allowing logical functions to control one small room, the floor of a building, or an entire building. All sensors receive their power from the DyNet network, and as they are fully remotely programmable, they can be configured to automate and control a virtually unlimited number of controlled outputs.

Product data

| General Information | | Full product name | |
|---------------------------|---|---------------------------------|-----------------|
| Remarks | Please download the Lighting - Product Data Sheet for more information and ordering options | Full product name | DUS360CR-DALI |
| CE mark | CE mark | Full product code | 871869688710300 |
| EU RoHS compliant | Yes | Order code | 913703500909 |
| Temperature | | Material Nr. (12NC) | 913703500909 |
| Ambient temperature range | 0 to +45 °C | Numerator - Quantity Per Pack | 1 |
| Product Data | | EAN/UPC - Product/Case | 8718696887103 |
| Order product name | DUS360CR-DALI | Numerator - Packs per outer box | 1 |
| | | EAN/UPC - Case | 8718696894101 |

Dynalite Sensors

Dimensional drawing

