



Electronic semiparallel ignitor for HID lamp circuits

SN 58 T15

HID ignitors for semi-parallel systems

Product data

Operating and Electrical				
Input Voltage	220 to 240 V	220 to 240 V		
Line Frequency	50 to 60 Hz	50 to 60 Hz		
Input Frequency	50 to 60 Hz			
Wiring				
Connector Type	Screw			
Temperature				
Ambient temperature range	-20 °C to 75 °C			
T-Case Maximum (Max)	80 ℃			
Mechanical and Housing				
Housing	Akulon S223	Akulon S223		

Approval and Application		
Approval Marks	CE marking ENEC certificate	
Product Data		
order product name	SN 58 T15	
ull product name	SN 58 T15	
ull product code	871016303333400	
rder code	913710010414	
laterial Nr. (12NC)	913710010414	
umerator - Quantity Per Pack	1	
AN/UPC - Product/Case	8710163148588	
lumerator - Packs per outer box	48	
AN/UPC - Case	8710163033334	

Datasheet, 2023, October 26 data subject to change

Electronic semi-parallel ignitor for HID lamp circuits

Dimensional drawing

Product	C1	A1	A2	B1
SN 58 T15	38.5 mm	85.5 mm	65.0 mm	41.5 mm

